



VSL-351

INTERCOM TERMINAL VSL-351

PRODUCT CODE 51045

FEATURES

- IP audio intercom terminal
- Tamper detection and attempted device removal notification
- Automated testing of speaker and microphone
- 316 type Stainless Steel
- Water and vandal resistant

SPECIFICATIONS

Speaker	1 x 4 Ω , 1 W RMS (power rating)
Speaker Amplifier	2 W
Max. Acoustic Output	88 dB SPL @ 1 m, 1 kHz (non-clipped) sine wave signal
Speaker Hole Size	42 holes x 4 – 7 mm (0.16 -0.28 in) diameter
Microphone	Electret condenser, omnidirectional, sensitivity -56 dB
Microphone Hole Size	1 hole x 2.5 mm (0.1 in) diameter
Audio Bandwidth	50 Hz – 7 kHz, -3 dB
Control Buttons	1 x piezo switch, red, 19 mm (0.75 in)
Auxiliary Functions	Relay contacts (2 x NO/NC), 30 V d.c./2 A - Optional module Tamper detection and attempted device removal notification Automated testing of speaker and microphone
Power Input	(12-36) V d.c. IEEE.802.3af (PoE) - Optional Module JPoE (24 v.d.c.) via optional JPP-6/12/240 - PoEA-1/6
Power Consumption	85 mA @ 24 V d.c. (idle) 220mA @ 24 V d.c.
Operating Temperature	(0 - 50)°C (32 - 122)°F
Operating Humidity	(10 – 95) % non-condensing
Cabling	4 pair UTP CAT-5/6, multi-strand, 24 AWG, 100 m (328 ft) max. 0.75 mm ² (0.0011 in ²) Figure 8 (Power feed if not JPoE)
Dimensions (WxHxD)	125 mm x 180 mm x 58 mm (4.92 in x 7.08 in x 2.28 in) 67 mm (2.64 in) min. mounted depth
Weight	0.75 kg (1.65 lb)
Material	316 stainless steel (2 mm / 0.08 in)
Finishes	Linish
Environment	Indoor and outdoor
Vandal Resistant	Yes, strong front panel, staggered speaker holes to prevent speaker damage
Mounting Options	Flush mount backbox (FWE-14), surface mount backbox (SWE-6\SWE-4SS), rainhood (SRH-1)
Mounting Holes	4 holes x 4.5 mm (0.18 in) diameter
Fixings	4 x M4 security torx screws