

CONTROLLER

JSC-5L-ATM | 52262



Features

	IP controller with audio threshold monitoring
	Upto 300 endpoints supported
	Supports high definition audio
	SATA hard drive (Enterprise)
	Segregated air-flow design for optimal unit cooling
	Redundant, hot swappable power supply

Package Contents

	JSC-5L-ATM controller
	Power cable (IEC 60320) C13 x 2
	Rack mount rails
	Audio Threshold Monitoring Software

Specifications

Endpoints Supported	250
RAM	8 GB DDR4 1.2 V 2133 MHz ECC Registered DIMM
Storage	1TB 3.5", 7200rpm, 32 MB, 3.0 Gb/s, NCQ SATA HDD
Chipset	Intel® C612 express Chipset
CPU	Intel Xeon E5-1620V4 4-Core, 8 Threads, 3.5GHz, 10MB Cache or similar
Indicators	LAN1 Link & Activity, LAN2 Link & Activity, Power, HDD
Dimensions (WxHxD)	437 mm x 89 mm x 648 mm
Weight	25 kg (55.12 lb)
Material	Steel, powder coated black
Mounting Options	2RU rack mounting, 660mm min rack depth
Power Input	(100 – 240) V a.c., (10 – 3.5) A a.c. 50-60Hz, IEC 60320 C14
Power Consumption	Redundant power supply capable of 740 W, 230 W (typical)
External Connections	2 x LAN (1 Gb), 4 x USB 2.0, VGA, RS-232, IPMI
Environment	Indoor
Operating Temperature	(5 – 35) °C (41 - 95)*F
Operating Humidity	(8 – 90) % non-condensing
Non-operating Temperature	(-40 – +60) °C (-40 - 140)*F
Non-operating Humidity	(5 – 95) % non-condensing