

CONTROLLER

JSC-5L | 51814



Features

	IP controller, large, more than 80 endpoints supported
	Includes JCCP server software for intercom devices to makeand receive calls
	Supports high definition audio
	SATA hard drive (Enterprise)
	Segregated air-flow design for optimal unit cooling
	Redundant, hot swappable power supply

Package Contents

	JSC-5L controller
	Power cable (IEC 60320) C13 x 2
	Rack mount rails
	JELinux and JCCP Software

Optional Packages

Software	Hardware
Intercom Report Server	Redundant HDDs—RAID 1
High Level Interface	
Event Controller	
Voice Annunciator	
High Availablility Package	
DAR	
SIP Proxy	

Specifications

Endpoints Supported	2000*
RAM	8GB 3200MHz DDR4 ECC Unbuffered DIMM 1Rx8 RAM
Storage	2TB 3.5" SATA 6Gbps 7200RPM 128MB Cache Hard Drive
Chipset	Intel® C252
CPU	Intel Xeon E-2336 Processor, 6-Core 2.90GHz 12MB cache 65W
Indicators	LAN1 Link & Activity, LAN2 Link & Activity, Power, HDD, System Status
Dimensions (WxHxD)	438 mm x 87 mm x 557.2 mm (17.24 in x 3.42 in x 21.94 in)
Weight	12 kg (26.45 lb)
Material	Steel, powder coated black
Mounting Options	2RU rack mounting, 580mm min rack depth
Power Input	(100 – 240) V a.c., (10 – 3.5) A a.c. 50-60Hz, IEC 60320 C14
Power Consumption	Acbel 800W redundant PS module
External Connections	2 x LAN (1 GB), 2 x USB 3.2 Gen 1, 2 x USB 3.2 Gen 2 and 4 x USB 2.0, VGA, RS232, IPMI
Operating Temperature	(0 to 40) °C (32 to 104) °F
Operating Humidity	(8 - 80) % (non-condensing)
Non-operating Temperature	(-40 to 60) °C (-40 to 140) °F
Non-operating Humidity	(20 – 95) % (non condensing)