

JED-0508 RELEASE NOTES C8 DECEMBER 2021

650 SERIES IP COMMUNICATION SYSTEM

SOFTWARE RELEASE CYCLE 8

The Jacques 650 series IP Communication System software suite DECEMBER 2021 release affects the following software modules:

- JELINUX
- Jacques Call Control Protocol (JCCP) Server
- Jacques 650 User Interface (J650UI)
- JEM-2 intercom firmware
- JEM-3 intercom firmware
- Digital Audio Recorder (DAR)
- Report Server
- Voice Annunciator (VANN)
- Event Controller (JEVNT)
- SIPPROXY
- Jacques Announcement Scheduler (JAS)

The following sections of this document provide a detailed list of features and improvements to Jacques 650 series IP communication system software modules since the last release.

JELINUX (V7)

JELinux is the operating system used on Jacques 650 series intercom controllers and servers. This section lists changes made to JELinux packages since version 7.97.21

NEW FEATURES

REF#	DETAIL	AFFECTED SOFTWARE PACKAGES
4140	syscfg attribute now supports use of quotes to enclose values that include spaces.	core
4140	customservice can run tcpdump as a service to capture network traffic and save to multilog. Used by support only.	core customservice daemontools jelogrotate

JCCPSERVER VERSION 7.97.42

The Jacques Call Control Protocol (JCCP) software module is the application that manages intercom endpoints and controls call. This section details new features and improvements added to JCCPSERVER software package since the release of V7.97.21.

NEW FEATURES

	Support for ending a ringing bridge call, if any of the answerers end the call	
3963	(i.e, pressing "Decline" ends call for all members of a bridge.	jccpserver
	Refer JCN-0407 (Enable Decline Call for VMS Bridges) rev1.0	

IMPROVEMENTS

REF#	DETAIL	AFFECTED SOFTWARE PACKAGES
3902	Fixed issue where intercoms could not originate calls due to resources not being released	jccpserver
4207	Jccpserver will no longer crash when DUMMYSLAVE is used	jccpserver
4463	IPM devices cannot be monitored by default. Refer JCN-0406.	jccpserver
4618	Improve handling of on-hold calls to prevent endpoint getting stuck in a call	jccpserver

When upgrading jccpserver V7.92 or below to V7.96 or higher, it is mandatory to install tools.jrp and redis.jrp (on 64-bit systems). To re-enable the ability for IPM devices to be monitored, refer to JCN-0406 (Allow IPM to be Monitored).

JEM-2 VERSION 7.97.42

JEM2 firmware is used on all JEM2 based audio intercoms including IPM-3X0, VSL-3XX, XXI-3X1 and HPU-5E2X models. This section details changes made to the JEM-2 firmware since the release of version V7.97.21.

IMPROVEMENTS

REF#	DETAIL	AFFECTED SOFTWARE PACKAGES
4479	Restore serial protocol operation. Earlier they were non operational and caused the device to reset	j2m797-42.bin
4677	JEM-2 no longer crashes when pressing the AUX button while being monitored	j2m797-42.bin

When upgrading JEM-2 devices to V7.97.42 it is important that ELI devices are not upgraded as they are no longer supported. For more information, refer to ECN-169.

DAR VERSION 7.97.42

Digital Audio Recorder (DAR) software module acts as a digital processor to perform audio echo cancellation, call recording, threshold alarm monitoring, covert monitoring, and background music streaming. This section lists the changes made to DAR software since the release of version V7.97.21.

NEW FEATURES

REF#	DETAIL	AFFECTED SOFTWARE PACKAGES
4669, 5107	Introduce darscope logging, which allows for packet monitoring of the DAR stream. Used by our support team only.	dar, darscope

IMPROVEMENTS

REF#	DETAIL	AFFECTED SOFTWARE PACKAGES
4835	Modification to prevent massive increase in CPU usage when using darscope logging	dar
5107	Loss of audio no longer occurs due to JEM-2 packet backlog	dar

JEM3 VERSION 7.97.42

JEM3 firmware is used on JEM3 based video intercom models including VMS-750, VES-741, VES-75K as well as the audio models VSL-74K and VSA-76K. This section details changes made to the JEM3 software since the last release version V7.97.21

IMPROVEMENTS

REF#	DETAIL	AFFECTED SOFTWARE PACKAGES
4412	Endpoints no longer reset after short calls	jem3rf2files-7.97.42.jel.x86_64.jrp

SIPPROXY 7.97.42

SIPPROXY is an additional feature that allows calls between Jacques 650 intercoms and SIP phones. This section details the changes made to SIPPROXY since the release of version V7.97.21.

IMPROVEMENTS

REF#	DETAIL	AFFECTED SOFTWARE PACKAGES
4828	Reduced sip registration time-out time to prevent multiple instances of the same device being registered	sipproxy
5095	Fixed false call reconnection after sipproxy hangs up call	sipproxy

If you are using sipproxy, it is strongly recommended to upgrade sipproxy to this version.

EVENT CONTROLLER VERSION 7.97.42

Jacques Event Controller is an additional feature that provides interfaces for the integration of external systems and products into the IP communications system. This section details changes made to Event Controller software since the last release, version V7.97.21.

IMPROVEMENTS

REF#	DETAIL	AFFECTED SOFTWARE PACKAGES
5210	Creating multiple announcements in quick succession will no longer cause event controller to lock up	jevent

REPORTSERVER VERSION 7.97.42

Report Server software module is used to keep track of all events that occur on the Jacques system controller. This section details the list of features added to Report Server since the release of version V7.97.21.

IMPROVEMENTS

REF#	DETAIL	AFFECTED SOFTWARE PACKAGES
3541	Fix output of eventcode 2015, Call Statistics. Previously the payload type was reported as the number of packets	reportserver

J650UI VERSION 8.24.28

The Jacques J650UI is a graphical interface designed to run on Windows. It may be used to instigate and receive calls from all devices in the system and displays maps and icons, representing intercoms deployed on site. Alarms, NCV, Cell to Cell, and Conference calling capabilities are also possible. This section details improvements added to J650UI software since the last release version V8.24.11.

IMPROVEMENTS

REF#	DETAIL	AFFECTED SOFTWARE PACKAGES
4894	Updated current suite of j650ui icons so that backgrounds are transparent. Refer JED-0431 (J650UI Configuration Reference Manual) rev1.5	J650UI-media-setup application
1868	Name of back to normal button for static emergency announcements can be changed. Refer JED-0431 (J650UI Configuration Reference Manual) rev1.5	J650UI-media-setup application
1868	Colour of active and non-active emergency announcements can be changed. Refer JED-0431 (J650UI Configuration Reference Manual) rev1.5	J650UI-media-setup application

SOFTWARE NOT AFFECTED BY RELEASE CYCLE 8

The following software applications do not have any changes since release cycle 7.

- Voice Annunciator (VANN) V7.97.42,
- Jacques Announcement Scheduler (JAS) V7.97.42
- HLI Development kit (JCCPDLL.DLL) V7.97.42

CONTACT DETAILS

 Ph:
 +61 7 3846 8400

 Email:
 info@jacques.com.au

 Website:
 www.jacques.com.au

 ABN:
 48 074 448 712